



Rocking Piston Compressors



KM-60HC



KM-120HC



KM-200HC

Features

- Oil-less piston
- Continuous or intermittent duty
- 230 Volt
- UL, CSA, & CE approved
- 2 m power cord
- Quiet operation
- 2 year limited warranty
- Thermal overload protection
- Ramped internal valve plate allows for restart under load after power failures

Model	KM-60HC	KM-120HC	KM-200HC
HP	1/4	1/2	3/4
Volt / Hz	230V / 50 Hz	230V / 50 Hz	230V / 50 Hz
Amp @ 0 PSI	0.92	1.25	2.6
Amp @ 20 PSI	1.3	1.6	3.1
Dimensions (cm)	18 x 16 x 20	24 x 16 x 20	27 x 17 x 24
Weight (kg)	7	9	13
Air Flow at PSI	LPM	LPM	LPM
0	98	135	186
5	80	125	178
10	78	118	168
15	70	113	160
20	69	108	158
25	65	100	150
30	61	95	147
40	53	87	130
50	45	78	120

Package Includes

- 2.8 kg/cm² pressure relief valve
- Intake air filter assembly
- Brass hose fitting

Box includes Model:

- KM-60HC
- KM-120HC
- KM-200HC

*Actual Results may vary based on power and environmental conditions

