AQUATICLEARTM

CLOG-RESISTANT CIRCULATOR

- 120V and 208-240V, single phase options
- Optional control panels include human-rated GFCI protection
- Unit only, Horizontal Float Kit, and mount options available
- Universal Mount Kit packages include Simple Swivel bracket (patent pending) that allows for easy rotation of the unit to direct flow of water
- NEW Shallow Water Install Kit allows AquatiClear to be installed in shallower water without creating an audible vortex, or suction sound. Purchased separately.





1/2, 3/4 & 1HP Available

NEW 75 ft. Power Cord on 1HP, 120V Units



Clean Current Technology (patent pending) Reduces Clogs



2-Year Warranty



Kasco.

ETL Listed to UL & CSA Standards

	VOLT (V)	MODEL	CORD LENGTH								
НР			25 FT	50 FT	NEW 75 FT	100 FT	150 FT	200 FT	250FT	300 FT	400 FT
UNIT ONLY PACKAGES - "C" (NO MOUNT)											
1/2	120	2400C	\$1,005	\$1,041	-	\$1,211	\$1,751	\$1,992	-	-	-
3/4	120	3400C	\$1,088	\$1,130	-	\$1,285	\$1,875	\$2,096	-	-	-
3/4	208-240	3400HC	-	\$1,176	-	\$1,308	\$1,914	\$2,107	\$2,254	\$2,351	\$2,824
1	120	4400C	-	\$1,282	\$1,388	\$1,792	\$2,466	\$2,790	-	-	-
1	208-240	4400HC	-	\$1,328	-	\$1,454	\$2,103	\$2,305	\$2,597	\$2,704	\$2,984
HORIZONTAL FLOAT PACKAGES - "CFM"											
1/2	120	2400CFM	\$1,500	\$1,536	-	\$1,706	\$2,246	\$2,487	-	-	-
3/4	120	3400CFM	\$1,583	\$1,625	-	\$1,780	\$2,370	\$2,591	-	-	-
3/4	208-240	3400HCFM	-	\$1,671	-	\$1,803	\$2,409	\$2,602	\$2,749	\$2,846	\$3,319
1	120	4400CFM	-	\$1,777	\$1,883	\$2,287	\$2,961	\$3,285	-	-	-
1	208-240	4400HCFM	-	\$1,823	-	\$1,949	\$2,598	\$2,800	\$3,092	\$3,199	\$3,479
UNIVERSAL MOUNT PACKAGES - "CDM" (CUSTOMER MUST SUPPLY PIPE)											
1/2	120	2400CDM	\$1,370	\$1,406	-	\$1,576	\$2,116	\$2,357	-	-	-
3/4	120	3400CDM	\$1,453	\$1,495	-	\$1,650	\$2,240	\$2,461	-	-	-
3/4	208-240	3400HCDM	-	\$1,541	-	\$1,673	\$2,279	\$2,472	\$2,619	\$2,716	\$3,189
1	120	4400CDM	-	\$1,647	\$1,753	\$2,157	\$2,831	\$3,155	-	-	-
1	208-240	4400HCDM	-	\$1,693	-	\$1,819	\$2,468	\$2,670	\$2,962	\$3,069	\$3,349

Product Notes:

1. Prices in bold have quick disconnect installed on power cords.

2. Part # is the model combined with cord length (ex. 3400CDM150).

3. Optional control panel allows timing to be managed from shore. See page 56 for details.

4. Without the Shallow Water Install kit, Kasco recommends installing AquatiClear more than 2 ft. below the surface.