

THE MOST ICE PROTECTION FOR YOUR PROPERTY





Prevents Ice Buildup and Improves Aquatic Environment



WARRANTY
2-YEAR WARRANTY
on 1/2, 3/4 & 1HP Units

CONTACT KASCO



Learn more about these systems and the difference they can make in your water treatment process.

+1.715.262.4488 kascomarine.com support@kascomarine.com

DE-ICERS

- · 220V, single phase options
- Includes (2) 6m mooring ropes
- Install with included mooring ropes or optional Universal or Industrial Mount Kits



DE-ICER PACKAGES

PART #	НР	VOLT (V)	PHASE	CORD LENGTH (m)
UNIT ONLY PACKAGES - "ED" (NO MOUNT)				
2400ED000	1/2	220	1	Stub Cord (1m)
2400ED010	1/2	220	1	10
2400ED030	1/2	220	1	30
3400ED000	3/4	220	1	Stub Cord (1m)
3400ED010	3/4	220	1	10
3400ED030	3/4	220	1	30
4400ED000	1	220	1	Stub Cord (1m)
4400ED010	1	220	1	10
4400ED030	1	220	1	30

Product Notes:

- 1. De-icers should be placed 1.2-1.8m below the surface, and .3m off the bottom.
- 2. Mounting option sold separately.
- 3. All Kasco De-icers ship completely assembled.

MOUNTING OPTIONS

PA	RT#	DESCRIPTION
243	3485	Universal Mount (Customer supplies 1 in. / 25 DN nominal threaded or unthreaded pipe and (8) 5/16 in. lag screws to mount base plate to dock. If a U-bolt Kit is used, these lag screws are not needed. Hardware for mount assembly is included.)
997	7108K	U-bolt Kit (For drill-free installation. Each kit includes 2 u-bolts and associated hardware.)

Product Notes:

- 1. Industrial Mounts are available for units in harsh environments.
- 2. Universal Mounts require (1) U-bolt Kit, Industrial Mounts require (2) U-bolt Kits.



Mooring Ropes (Included)



Universal Mount (Purchased Separately)