



MOVING WATER FORWARD, SINCE 1968

DE-ICERS

Kasco De-icers push warm bottom water up to the surface creating an ice-free area of protection around your boat, dock, or pier. Kasco De-icers create more thrust than any other competitor, meaning more open water to better protect your property.

THE MOST ICE PROTECTION FOR YOUR PROPERTY



Contact us today to learn more | +1.715.262.4488 | kascomarine.com

THE BEST-SELLING, MOST POWERFUL DE-ICER

HP

1/2, 3/4, & 1HP
Available

CE

CE Marked



Prevents Ice Buildup and
Improves Aquatic Environment



WARRANTY

2-YEAR WARRANTY

on 1/2, 3/4 & 1HP Units

CONTACT KASCO



Learn more about these systems
and the difference they can make
in your water treatment process.

+1.715.262.4488
kascomarine.com
support@kascomarine.com

DE-ICERS

- 220V, single phase options
- Includes (2) 6m mooring ropes
- Install with included mooring ropes or optional Universal or Industrial Mount Kits



DE-ICER PACKAGES

PART NUMBER	HP	VOLT (V)	PHASE	CORD LENGTH (m)
2400ED000	1/2	220	1	Stub Cord (1m)
2400ED010	1/2	220	1	10
2400ED030	1/2	220	1	30
3400ED000	3/4	220	1	Stub Cord (1m)
3400ED010	3/4	220	1	10
3400ED030	3/4	220	1	30
4400ED000	1	220	1	Stub Cord (1m)
4400ED010	1	220	1	10
4400ED030	1	220	1	30

Product Notes:

1. De-icers should be placed 1.2-1.8m below the surface, and .3m off the bottom.
2. Mounting option sold separately.
3. All Kasco De-icers ship completely assembled.

MOUNTING OPTIONS

PART NUMBER	DESCRIPTION	CUSTOMER-SUPPLIED ITEMS
243485	Universal Mount	Customer supplies 1 in. / 25 DN nominal threaded or unthreaded pipe and (8) 5/16 in. lag screws to mount base plate to dock. To install mount without drilling into dock, use available U-bolt Kit instead of lag screws.
243478	Universal Mount with Patented Simple Swivel Bracket	Customer supplies 1 in. / 25 DN nominal threaded or unthreaded pipe and (8) 5/16 in. lag screws to mount base plate to dock. To install mount without drilling into dock, use available U-bolt Kit instead of lag screws.
997108K	U-bolt Kit for drill-free installation (Each kit includes 2 U-bolts and associated hardware.)	-

Product Notes:

1. Pipes should not exceed 3m and can be threaded or unthreaded (supplied by customer).
2. Industrial Mounts (with and without the Simple Swivel bracket) are available for units in harsh environments. Visit kascomarine.com to learn more.



Mooring Ropes
(Included)



Universal Mount
(Purchased Separately)



Patented Simple
Swivel bracket allows
unit to be rotated.



U-bolt Kit shown
attaching mount
base to dock piling.