

AQUATICLEAR™

CLOG-RESISTANT CIRCULATOR

- 120V and 208-240V, single phase options
- Unit only, Horizontal Float, and Universal Mount options available
- Universal Mounts include the Simple Swivel bracket.
- Shallow Water Install Kit available.
- Manage from shore with optional human-rated, GFCI-protected control panel. See page 54.



1/2, 3/4, & 1HP
Available



Crown-like Prop Guard
Decreases Clogging from Debris



2-Year Warranty



ETL Listed to UL
& CSA Standards

HP	VOLT (V)	MODEL	CORD LENGTH									
			25 FT	50 FT	75 FT	100 FT	150 FT	200 FT	250FT	300 FT	400 FT	500 FT
UNIT ONLY PACKAGES - "C" (NO MOUNT)												
1/2	120	2400C	\$1,045	\$1,083	-	\$1,259	\$1,821	\$2,072	-	-	-	-
3/4	120	3400C	\$1,132	\$1,175	-	\$1,336	\$1,950	\$2,180	-	-	-	-
3/4	208-240	3400HC	-	\$1,223	-	\$1,360	\$1,991	\$2,191	\$2,344	\$2,445	\$2,937	Inquire
1	120	4400C	-	\$1,359	\$1,471	\$1,900	\$2,514	\$2,957	-	-	-	-
1	208-240	4400HC	-	\$1,381	-	\$1,512	\$2,187	\$2,397	\$2,701	\$2,812	\$3,103	Inquire
HORIZONTAL FLOAT PACKAGES - "CFM"												
1/2	120	2400CFM	\$1,545	\$1,583	-	\$1,759	\$2,321	\$2,572	-	-	-	-
3/4	120	3400CFM	\$1,632	\$1,675	-	\$1,836	\$2,450	\$2,680	-	-	-	-
3/4	208-240	3400HCFM	-	\$1,723	-	\$1,860	\$2,491	\$2,691	\$2,844	\$2,945	\$3,437	Inquire
1	120	4400CFM	-	\$1,859	\$1,971	\$2,400	\$3,014	\$3,457	-	-	-	-
1	208-240	4400HCFM	-	\$1,881	-	\$2,012	\$2,687	\$2,897	\$3,201	\$3,312	\$3,603	Inquire
UNIVERSAL MOUNT PACKAGES - "CDM" (CUSTOMER MUST SUPPLY PIPE)												
1/2	120	2400CDM	\$1,417	\$1,455	-	\$1,631	\$2,193	\$2,444	-	-	-	-
3/4	120	3400CDM	\$1,504	\$1,547	-	\$1,708	\$2,322	\$2,552	-	-	-	-
3/4	208-240	3400HCDM	-	\$1,595	-	\$1,732	\$2,363	\$2,563	\$2,716	\$2,817	\$3,309	Inquire
1	120	4400CDM	-	\$1,731	\$1,843	\$2,272	\$2,886	\$3,329	-	-	-	-
1	208-240	4400HCDM	-	\$1,753	-	\$1,884	\$2,559	\$2,769	\$3,073	\$3,184	\$3,475	Inquire

Product Notes:

1. Prices in bold have quick disconnect installed on power cords.
2. Part # is the model combined with cord length (ex. 3400CDM150).
3. If AquatiClear is installed less than 1.5 ft. below the surface, a Shallow Water Install Kit is recommended. See page 35.
4. Solar-powered option available. Contact Kasco for details.



NEVER enter the water with electrical equipment connected and / or in operation.