

AQUATICLEAR™

CLOG-RESISTANT CIRCULATOR

- 120V and 208-240V, single phase options
- Purchased as stand-alone unit, or as part of a Horizontal Float or Universal Mount package
- Universal Mounts include the Simple Swivel bracket
- Shallow Water Install Kit available
- Manage from shore with optional human-rated, GFCI-protected control panel (see page 62)



1/2, 3/4, & 1HP Available



Crown-like Prop Guard Decreases Clogging



2-Year Warranty



ETL Listed to UL & CSA Standards

HP	VOLT (V)	MODEL	CORD LENGTH									
			25 FT	50 FT	75 FT	100 FT	150 FT	200 FT	250 FT	300 FT	400 FT	500+ FT
UNIT ONLY PACKAGES - "C" (NO MOUNT)												
1/2	120	2400C	\$1,068	\$1,104	-	\$1,292	\$1,757	\$1,929	-	-	-	-
3/4	120	3400C	\$1,177	\$1,218	-	\$1,400	\$1,882	\$2,044	-	-	-	-
3/4	208-240	3400HC	-	\$1,217	-	\$1,399	\$1,943	\$2,136	\$2,364	\$2,464	\$2,956	Inquire
1	120	4400C	-	\$1,401	\$1,517	\$1,850	\$2,477	\$2,851	-	-	-	-
1	208-240	4400HC	-	\$1,447	-	\$1,623	\$2,104	\$2,315	\$2,702	\$2,813	\$3,103	Inquire
UNIT AND HORIZONTAL FLOAT PACKAGES - "CFM"												
1/2	120	2400CFM	\$1,568	\$1,604	-	\$1,792	\$2,257	\$2,429	-	-	-	-
3/4	120	3400CFM	\$1,677	\$1,718	-	\$1,900	\$2,382	\$2,544	-	-	-	-
3/4	208-240	3400HCFM	-	\$1,717	-	\$1,899	\$2,443	\$2,636	\$2,864	\$2,964	\$3,456	Inquire
1	120	4400CFM	-	\$1,901	\$2,017	\$2,350	\$2,977	\$3,351	-	-	-	-
1	208-240	4400HCFM	-	\$1,947	-	\$2,123	\$2,604	\$2,815	\$3,202	\$3,313	\$3,603	Inquire
UNIT AND UNIVERSAL MOUNT PACKAGES - "CDM" (CUSTOMER MUST SUPPLY PIPE)												
1/2	120	2400CDM	\$1,440	\$1,476	-	\$1,664	\$2,129	\$2,301	-	-	-	-
3/4	120	3400CDM	\$1,549	\$1,590	-	\$1,772	\$2,254	\$2,416	-	-	-	-
3/4	208-240	3400HCDM	-	\$1,589	-	\$1,771	\$2,315	\$2,508	\$2,736	\$2,836	\$3,328	Inquire
1	120	4400CDM	-	\$1,773	\$1,889	\$2,222	\$2,849	\$3,223	-	-	-	-
1	208-240	4400HCDM	-	\$1,819	-	\$1,995	\$2,476	\$2,687	\$3,074	\$3,185	\$3,475	Inquire

Product Notes:

1. Prices in bold have quick disconnect installed on power cords.
2. Part # is the model combined with cord length (ex. 3400CDM150).
3. If AquatiClear is installed less than 1.5 ft. below the surface, a Shallow Water Install Kit is recommended. See page 35.



NEVER enter the water with electrical equipment connected and / or in operation.