

AQUATICLEAR™

CLOG-RESISTANT CIRCULATOR

- 120V and 208-240V, single phase options
- Purchased as stand-alone unit, or as part of a Horizontal Float or Universal Mount package
- Universal Mounts include the Simple Swivel bracket
- Shallow Water Install Kit available
- Manage from shore with optional human-rated, GFCI-protected control panel (see page 66)



1/2, 3/4, & 1HP Available



Crown-like Prop Guard Decreases Clogging



2-Year Warranty



ETL Listed to UL & CSA Standards

HP	VOLT (V)	MODEL	CORD LENGTH									
			25 FT	50 FT	75 FT	100 FT	150 FT	200 FT	250 FT	300 FT	400 FT	500+ FT
UNIT ONLY PACKAGES - "C" (NO MOUNT)												
1/2	120	2400C	\$1,156	\$1,194	-	\$1,392	\$1,880	\$2,060	-	-	-	-
3/4	120	3400C	\$1,275	\$1,318	-	\$1,509	\$2,015	\$2,185	-	-	-	-
3/4	208-240	3400HC	-	\$1,317	-	\$1,508	\$2,079	\$2,282	\$2,482	\$2,587	\$3,104	Inquire
1	120	4400C	-	\$1,501	\$1,623	\$2,022	\$2,631	\$3,024	-	-	-	-
1	208-240	4400HC	-	\$1,549	-	\$1,734	\$2,239	\$2,461	\$2,837	\$2,954	\$3,258	Inquire
UNIT AND HORIZONTAL FLOAT PACKAGES - "CFM"												
1/2	120	2400CFM	\$1,691	\$1,729	-	\$1,927	\$2,415	\$2,595	-	-	-	-
3/4	120	3400CFM	\$1,810	\$1,853	-	\$2,044	\$2,550	\$2,720	-	-	-	-
3/4	208-240	3400HCFM	-	\$1,852	-	\$2,043	\$2,614	\$2,817	\$3,017	\$3,122	\$3,639	Inquire
1	120	4400CFM	-	\$2,036	\$2,158	\$2,557	\$3,166	\$3,559	-	-	-	-
1	208-240	4400HCFM	-	\$2,084	-	\$2,269	\$2,774	\$2,996	\$3,372	\$3,489	\$3,793	Inquire
UNIT AND UNIVERSAL MOUNT PACKAGES - "CDM" (CUSTOMER MUST SUPPLY PIPE)												
1/2	120	2400CDM	\$1,621	\$1,659	-	\$1,857	\$2,345	\$2,525	-	-	-	-
3/4	120	3400CDM	\$1,740	\$1,783	-	\$1,974	\$2,480	\$2,650	-	-	-	-
3/4	208-240	3400HCDM	-	\$1,782	-	\$1,973	\$2,544	\$2,747	\$2,947	\$3,052	\$3,569	Inquire
1	120	4400CDM	-	\$1,966	\$2,088	\$2,487	\$3,096	\$3,489	-	-	-	-
1	208-240	4400HCDM	-	\$2,014	-	\$2,199	\$2,704	\$2,926	\$3,302	\$3,419	\$3,723	Inquire

Product Notes:

1. Prices in bold have quick disconnect installed on power cords.
2. Part number is the model combined with cord length (ex. 3400CDM150).
3. If AquatiClear is installed less than 1.5 ft. below the surface, a Shallow Water Install Kit is recommended. See page 39.



NEVER enter the water with electrical equipment connected and / or in operation.