

# CONTROL PANELS

Control panels allow energy-saving automatic control of your Kasco unit. Select your desired settings, and the control panel will handle the rest. Kasco control panels are approved and listed to the most stringent UL and CSA standards to deliver the safety and performance you need.



## IMPORTANT SAFETY NOTES



NEVER Enter the Water  
While Equipment is  
Operating or Plugged in



Never Bypass  
GFCI-Protected Circuit



Test GFCI Every 30 Days  
After Unit Installation



For Electrical Wiring, Follow  
All Codes and Consult  
Qualified Electrician

PART #	MODEL	USE WITH	CONTROL FUNCTION	GROUND FAULT PROTECTION	MSRP
125250	C-25	120V, 1/2, 3/4, and 1HP fountains, AquatiClear Circulators, and surface aerators	(1) 24-HR timer and photocell	6 milliamp (human-rated)	\$351
176005	C-85	208-240V, 3/4, 1, and 2HP fountains and surface aerators 208-240V, 3/4, 1, and 2HP AquatiClear Circulators	(2) 24-HR timers	6 milliamp (human-rated)	\$1,942
176090	C-95	208-240V, 3 and 5HP fountains and surface aerators	(2) 24-HR timers	6 milliamp (human-rated)	\$1,946
176332	C-220	208-240V, 3/4, and 1HP AquatiClear Circulators 208-240V, 3/4, 1, and 2HP surface aerators	(1) 24-HR timer	6 milliamp (human-rated)	\$1,290
176333	C-230	208-240V, 3 and 5HP surface aerators	(1) 24-HR timer	6 milliamp (human-rated)	\$1,290
176210	CA-3235	208-240V, 2, 3, and 5HP three phase surface aerators	(1) 24-HR timer	30 milliamp (equipment-rated)	\$3,296
176200	CF-3235	208-240V, 2, 3, and 5HP three phase fountains and surface aerators	(2) 24-HR timers	5 milliamp (human-rated)	\$4,340
176204	CF-3075	208-240V, 7.5HP three phase fountains	(2) 24-HR timers	5 milliamp (human-rated)	\$4,062

### Product Notes:

1. The C-25 has one timer to operate the unit and a photocell to operate the lights.
2. The C-85, C-95, CF-3235, and CF-3075 have two timers, one for the unit and one for the lights. These panels do not include a photocell.
3. Power cord lengths can be up to 500 ft. Never add any additional cord, as that will void warranty, void ETL approval, and can cause nuisance tripping of the GFCI.
4. Any unauthorized modifications to any Kasco control panel will void the UL listing and Kasco warranty.
5. Kasco includes a GFCI tester with all 1/2, 3/4, and 1HP units that can be used to test an outlet prior to use.