

CONTROL PANELS

Control panels allow energy-saving automatic control of your Kasco unit. Select your desired settings, and the control panel will handle the rest.



- Panels are included for J and VFX Series Fountains
- Panels are optional for surface aerators except 2.3, 3.3, and 5.3HP units (non-"U" units)
- Surface aerator control panels depend on if lights are used (refer to the table below)

PART #	MODEL	USE WITH				CONTROLLED FUNCTION	BASED ON	GROUND FAULT PROTECTION	MSRP
		DE-ICER (Optional)	FOUNTAIN (J & VFX SERIES) (Included)	SURFACE AERATOR (Optional)	AQUATICLEAR (Optional)				
120V, SINGLE PHASE UNITS									
110225	C-10	1/2, 3/4, 1HP	-	-	-	Unit only	Thermostat	NA	\$150
120350	C-20	1/2, 3/4, 1HP	-	-	-	Unit only	Timer and thermostat	NA	\$320
125250	C-25	-	1/2**, 3/4, 1HP	1/2, 3/4, 1HP	1/2, 3/4, 1HP	Unit and lights	(1) Timer for unit (1) Photocell for lights	6-milliamp (human-rated)	\$351
208-240V, SINGLE PHASE UNITS									
176006	C-85	-	3/4, 1, 2HP	3/4, 1, 2HP <i>with lights</i>	-	Units and lights	(1) Timer for unit (1) Timer for lights	6-milliamp (human-rated)	\$2,273
176091	C-95	-	3, 5HP	3, 5HP <i>with lights</i>	-	Unit and lights	(1) Timer for unit (1) Timer for lights	6-milliamp (human-rated)	\$2,270
176332	C-220	3/4, 1HP	-	3/4, 1HP, 2HP	3/4, 1HP	Unit only	(1) Timer for unit	6-milliamp (human-rated)	\$1,290
176333	C-230	-	-	3, 5HP	-	Unit only	(1) Timer for unit	6-milliamp (human-rated)	\$1,338
208-240V, THREE PHASE UNITS									
176210	CA-3235	-	-	2, 3, 5HP*	-	Unit only	(1) Timer for unit	30-milliamp (equipment-rated)	\$3,296
176200	CF-3235	-	2, 3, 5HP	2, 3, 5HP <i>with lights</i>	-	Unit and lights	(1) Timer for unit (1) Timer for lights	5-milliamp (human-rated)	\$4,340
176204	CF-3075	-	7.5HP***	-	-	Unit and lights	(1) Timer for unit (1) Timer for lights	5-milliamp (human-rated)	\$4,062

*2.3, 3.3, and 5.3HP surface aerators include a CA-3235 control panel. Control panels are optional for all other surface aerator models (including "U" models).

**1/2HP is only offered for VFX Series Fountains.

***7.5HP is only offered for J Series Fountains.

Product Notes:

1. Test GFCI every 30 days after unit installation.
2. For electrical wiring, follow all codes and consult qualified electrician.



NEVER enter the water with electrical equipment connected and / or in operation.