

# CONTROL PANELS

Control panels allow energy-saving automatic control of your Kasco unit.

Select your desired settings, and the control panel will handle the rest.

- Panels are included for J and VFX Series Fountains
- Panels are optional for surface aerators except 2.3, 3.3, and 5.3HP units (non-“U” units)
- Surface aerator control panels will depend on voltage of the unit and if lights are used (refer to the table below)



PART NUMBER	MODEL	USE WITH				CONTROLLED FUNCTION	BASED ON	GROUND FAULT PROTECTION	MSRP
		DE-ICER (Optional)	FOUNTAIN (J & VFX SERIES) (Included)	SURFACE AERATOR (Optional)	AQUATICLEAR (Optional)				
120V, SINGLE PHASE UNITS									
110225	C-10	1/2, 3/4, 1HP	-	-	-	Unit only	Thermostat	N/A	\$150
120350	C-20	1/2, 3/4, 1HP	-	-	-	Unit only	Timer and thermostat	N/A	\$335
125250	C-25	-	1/2**, 3/4, 1HP	1/2, 3/4, 1HP	1/2, 3/4, 1HP	Unit and lights	(1) Timer for unit (1) Photocell for lights	6-milliamp (human-rated)	\$420
208-240V, SINGLE PHASE UNITS									
176006	C-85	-	3/4, 1, 2HP	3/4, 1, 2HP with lights	-	Unit and lights	(1) Timer for unit (1) Timer for lights	6-milliamp (human-rated)	\$2,369
176091	C-95	-	3, 5HP	3, 5HP with lights	-	Unit and lights	(1) Timer for unit (1) Timer for lights	6-milliamp (human-rated)	\$2,366
176332	C-220	3/4, 1HP	-	3/4, 1HP, 2HP	3/4, 1HP	Unit only	(1) Timer for unit	6-milliamp (human-rated)	\$1,350
176333	C-230	-	-	3, 5HP	-	Unit only	(1) Timer for unit	6-milliamp (human-rated)	\$1,400
208-240V, THREE PHASE UNITS									
176210	CA-3235	-	-	2, 3, 5HP*	-	Unit only	(1) Timer for unit	30-milliamp (equipment-rated)	\$3,500
176200	CF-3235	-	2, 3, 5HP	2, 3, 5HP with lights	-	Unit and lights	(1) Timer for unit (1) Timer for lights	5-milliamp (human-rated)	\$4,450
176204	CF-3075	-	7.5HP***	-	-	Unit and lights	(1) Timer for unit (1) Timer for lights	5-milliamp (human-rated)	\$4,150

\*2.3, 3.3, and 5.3HP surface aerators include a CA-3235 control panel. Control panels are optional for all other surface aerator models (including “U” models).

\*\*1/2HP is only offered for VFX Series Fountains.

\*\*\*7.5HP is only offered for J Series Fountains.

Product Notes:

1. Test GFCI every 30 days after unit installation.
2. For electrical wiring, follow all codes and consult qualified electrician.



NEVER enter the water with electrical equipment connected and / or in operation.