



AQUATICLEAR™ CIRCULATORS

This clog-resistant circulator produces water movement to keep docks, marinas, and other areas clear of floating weeds, algae, and debris. AquatiClear features a crown-like composite prop guard allowing for continuous operation and less maintenance.



CLOG-RESISTANT WATERFRONT MANAGEMENT

Contact us today to learn more | 715.262.4488 | kascomarine.com

BEFORE & AFTER



WARRANTY

2-YEAR WARRANTY

on 1/2, 3/4, & 1HP Units

LIFETIME WARRANTY

on Universal & Industrial Mount Kits

3-YEAR WARRANTY

on Horizontal Float

CONTACT KASCO



Learn more about these systems and the difference they can make in your water treatment process.

715.262.4488

kascomarine.com

support@kascomarine.com

AQUATICLEAR

- 120V and 208-240V, single phase options
- Purchased as stand-alone unit, or as part of a Horizontal Float or Universal Mount package
- Universal Mounts include the Simple Swivel bracket
- Complete packages are ETL Listed to UL and CSA standards



1/2, 3/4, & 1HP Available



Crown-like Prop Guard Decreases Clogging



Clean Current Technology™



2-year Warranty

SHALLOW WATER INSTALL KIT

With the Shallow Water Install Kit, AquatiClear can be installed in shallower water without disrupting the lake or pond bottom and without creating a loud suction sound (ventilation). Kits are purchased separately.



AQUATICLEAR PACKAGES

MODEL	HP	VOLT (V)	PHASE	AMPS	THRUST (LBS)	OPTIONAL CONTROL PANEL
UNIT ONLY PACKAGES - "C" (NO MOUNT)						
2400C	1/2	120	1	5.4	30	C-25
3400C	3/4	120	1	6.6	36	C-25
3400HC	3/4	208-240	1	3.1	36	C-220
4400C	1	120	1	9.1	41	C-25
4400HC	1	208-240	1	4.5	41	C-220
UNIT AND HORIZONTAL FLOAT PACKAGES - "CFM"						
2400CFM	1/2	120	1	5.4	30	C-25
3400CFM	3/4	120	1	6.6	36	C-25
3400HCFM	3/4	208-240	1	3.1	36	C-220
4400CFM	1	120	1	9.1	41	C-25
4400HCFM	1	208-240	1	4.5	41	C-220
UNIT AND UNIVERSAL MOUNT PACKAGES - "CDM" (CUSTOMER MUST SUPPLY PIPE)						
2400CDM	1/2	120	1	5.4	30	C-25
3400CDM	3/4	120	1	6.6	36	C-25
3400HCDM	3/4	208-240	1	3.1	36	C-220
4400CDM	1	120	1	9.1	41	C-25
4400HCDM	1	208-240	1	4.5	41	C-220

Product Notes:

1. Package includes motor unit, power cord, mounting option, and optional control panel.
2. Cord lengths available in various lengths from 25 ft. - 400 ft., according to HP and voltage. Call Kasco for details.
3. Optional control panels allow timing to be managed from shore.
4. Without the Shallow Water Install Kit, install AquatiClear 1.5 ft. or more below the surface to prevent audible ventilation.
5. Do not direct water flow downward as it could disturb bottom sediment. Check for local guidelines.