



POTABLE WATER TANK MIXERS

CertiSafe™ Active Tank Mixers blend drinking water in tanks and reservoirs quickly and efficiently. These powerful mixing systems create an environment homogeneous in chemical concentration and temperature, improving water quality from tank to tap.

THERE'S SORT OF SAFE, OR THERE'S CERTISAFE



Contact us today to learn more | 715.262.4488 | kascomarine.com/certisafe

MOUNTING OPTIONS



SUSPENDED MOUNT

Designed for use in elevated or standpipe tanks



FLOOR MOUNT

Designed for use in ground storage tanks



PIPE MOUNT

Designed for use in irregular and unique tank structures



WARRANTY

3-YEAR WARRANTY

on 1/2, 3/4, 1, & 2HP units

Optional 5-Year Extended Warranty

CONTACT KASCO



Learn more about these systems and the difference they can make in your water treatment process.

715.262.4488
kascomarine.com
support@kascomarine.com

WATER QUALITY CHALLENGES

When drinking water is not mixed quickly, evenly, and continuously, it can fall out of EPA compliance, putting the health and safety of your community in danger. Common problems include:

- Residual loss
- Biofilm buildup
- Nitrification
- Thermal and chemical stratification

THE SOLUTION

By creating strong, consistent circulation, CertiSafe™ Tank Mixers quickly and evenly move water while eliminating common water quality problems. Available in several HP sizes, multiple mounting orientations, and various control panels, there is a CertiSafe Mixing solution for nearly every size and style of tank.



CERTISAFE PACKAGES

TANK SIZE	MODEL	VOLT (V)	PHASE	HP	CABLE LENGTH (FT)	AMPS
Up to 1MG	2400C61	120	1	1/2	50	5.7
					75	
Up to 2.5MG	3400C61	120	1	3/4	50	7
					75	
	3400HC61	208-240	1	3/4	50	3,5
					75	
Up to 5MG	4400C61	120	1	1	50	9.1
					75	
	4400HC61	208-240	1	1	50	4.5
					75	
5MG & Over	8400C61	208-240	1	2	50	9
					75	

Product Notes:

1. Part # is the mixer model combined with "0" + cord length (ex. 2400C61050)
2. Mounting option sold separately.
3. Control panel option sold separately.

