# HYDRAFORCE LIFT STATION AGITATOR POST MOUNT SYSTEM

#### **OVERVIEW**

- System includes rocking piston compressor, mounting base, diffuser(s)
- Weighted air tubing standard on 1-3 diffuser systems
- Designed for 24-hour operation with minimal maintenance
- Inlet air filter visual maintenance indicator
- Patent-pending noise-cancelling design to dramatically reduce compressor sound

#### COMPRESSOR

- Continuous-duty rated
- Ramped reed valve
- Heat-resistant tubing
- Paper air filter element
- UL/CSA Recognized

#### Teich-Aire KM-60C

- 1/4HP oilless piston compressor
- 115V (KM-60C) 2.2 amps, 3.8 CFM @ 0 psi
- 40 psi pressure relief valve

#### Teich-Aire KM-120C

- 1/2HP oilless piston compressor
- 115V (KM-120C) 3.0 amps, 5.5 CFM @ 0 psi
- 40 psi pressure relief valve
- Can supply up to 3 diffuser heads

# **INSTALLATION KIT**

- 316 stainless steel chain
- 316 stainless steel eyebolts
- 316 stainless steel snap hooks
- Concrete anchors & installation tool
- 25' 316 stainless steel suspension cable
- Brass cable adjuster
- Tube fitting kit

# *HYDRAFORCE*

# POST MOUNT

- Accommodates one 1/4 or 1/2HP compressor
- Powder-coated aluminum cabinet
- Internal sound-dampening foam
- Mounting template for 4x4 post or wall
- Hinged top and front cover for easy access
- 110 CFM cooling fan with guard
- 11.5" x 11.4" x 18.5"
- 6' pigtail with plug

# DIFFUSER

- Independently tested to produce the most flow
- Self-weighted stainless steel base
- Proprietary linear low-density polyethylene & rubber diffuser hose
- 23" x 15.5" assembled
- Diffuser hose sits 6" above bottom of base
- Check valve

# SURESINK WEIGHTED TUBING


• 3/8" x 50' roll(s)

# WARRANTY

2 years

HYDRAFORCE LIFT STATION POST MOUNT CUT SHEET

800 Deere Rd. Prescott, WI 54021 | 715.262.4488 | sales@kascomarine.com | kascomarine.com



# HYDRAFORCE LIFT STATION AGITATOR POST MOUNT SYSTEM

#### 60 Hz STANDARD SYSTEM OVERVIEW

Model Number	Compressor(s)	# of Diffusers	Voltage/Phase	Running Amps @ 5 psi	Number of 50-ft. rolls of 3/8" tubing included
LS-100	KM-60C (1/4HP)	1	120V / 1	2.5	1
LS-150	KM-60C (1/2HP)	1	120V / 1	3.5	1
LS-200	KM-60C (1/2HP)	2	120V / 1	3.5	2
LS-300	KM-60C (1/2HP)	3	120V / 1	3.5	3



HYDRAFORCE LIFT STATION POST MOUNT CUT SHEET

800 Deere Rd. Prescott, WI 54021 | 715.262.4488 | sales@kascomarine.com | kascomarine.com