



## 2.3HJF FOUNTAIN

### OVERVIEW

- Complete package includes motor unit, control panel, float with screens, mooring lines, cable, five interchangeable nozzles
- Total package Listed by ETL to UL/CSA standards
- Intake near surface allows for shallow operation
- Saltwater compatible
- Packaged for convenient shipping
- Optional lighting available

### FLOAT


- UV-resistant polyethylene
- Single-piece float
- Series 300 stainless steel hardware
- Series 300 stainless steel bottom screen
- Three 50' braided nylon mooring ropes

### FOUNTAIN COMPONENTS

- Custom thermoplastic impeller
- UV-resistant thermoplastic cone and fountain housing
- Stainless steel base plate
- Series 300 stainless steel hardware
- Five thermoplastic nozzles
- Twist on/off nozzles for easy pattern changes

### POWER CABLE

- 4 wire (L1, L2, L3, G)
- Quick Disconnect standard
- Stainless steel strain relief standard
- 6' protective stainless steel flex sleeving standard (optional for entire cord length)
- Cable is UL, CSA, & NEC rated for underwater use



### Dimensions

Float diameter: 37.5"

Unit height with float: 21.5"

### MOTOR UNIT

- 2HP, 460Vac operating voltage, three phase
- Class B insulation
- 1750 RPM
- Oil cooled
- Continuous duty rated
- 17mm top and 20mm bottom bearings
- Fully unitized heavy-duty carbon-ceramic mechanical seal
- Series 300 stainless steel can
- Cast stainless steel motor top
- Sacrificial anode installed on 316 stainless shaft

### CONTROL PANEL

- UL 508 Listed
- NEMA type 3R/4X thermoplastic enclosure
- Equipment-rated GFCI protection
- Surge protector
- Motor starter with adjustable overload
- Hand-Off-Auto switch
- 24-hour mechanical timers (fountains & lights)
- Terminal block wiring
- 5-wire power required (L1, L2, L3, N, G)

# 2.3HJF FOUNTAIN

## OVERVIEW

HP	Voltage / Phase / Hz	Running Amps	Lock Rotor Amps	Suggested Pond Size (SA)	Min. Depth of Operation (in.)
2	460V / 3 / 60	3.6	40	Up to 1*	20"

\*Surface Acreage; also consider pond shape, depth, and oxygen demand.

## MODEL SPECIFICATIONS


Model	Cord Length (ft.)	Cord Gauge
2.3HJF050	50	14/4
2.3HJF100	100	14/4
2.3HJF150	150	14/4
2.3HJF200	200	14/4
2.3HJF250	250	14/4
2.3HJF300	300	14/4
2.3HJF400**	400	14/4
2.3HJF500**	500*	14/4

\*500' and longer cords available by custom order only.


\*\*Ships motor freight only.




## INCLUDED PATTERNS




Birch  
11' H x 10' W




Spruce  
21' H x 10' W




Redwood  
22' H x 6' W



Linden  
(Blue Nozzle)  
15.5' H x 38' W



Balsam  
(Blue Nozzle)  
14' H x 32' W

**NOTE**  For additional patterns, ask about Premium Nozzles.

