




3.3HJF FOUNTAIN

OVERVIEW

- Complete package includes motor unit, control panel, float with screens, mooring lines, cable, five interchangeable nozzles
- Total package Listed by ETL to UL/CSA standards
- Intake near surface allows for shallow operation
- Saltwater compatible
- Packaged for convenient shipping
- Optional lighting available



Dimensions

Float diameter: 43"

Unit height with float: 24"

FLOAT

- UV-resistant polyethylene
- Single-piece float
- Series 300 stainless steel hardware
- Series 300 stainless steel top and bottom screen
- Three 50' braided nylon mooring ropes

FOUNTAIN COMPONENTS

- Custom thermoplastic impeller
- UV-resistant thermoplastic cone and fountain housing
- Stainless steel base plate
- Series 300 stainless steel hardware
- Five thermoplastic nozzles
- Twist on/off nozzles for easy pattern changes

POWER CABLE

- 4 wire (L1, L2, L3, G)
- Quick Disconnect standard
- Stainless steel strain relief standard
- 6' protective stainless steel flex sleeving standard (optional for entire cord length)
- Cable is UL, CSA & NEC rated for underwater use

MOTOR UNIT

- 3HP, 460Vac operating voltage, three phase
- Class B insulation
- 1750 RPM
- Oil cooled
- Continuous duty rated
- 17mm top and 20mm bottom bearings
- Thermal overload protection
- Fully unitized heavy-duty carbon-ceramic mechanical seal
- Series 300 stainless steel can
- Cast stainless steel motor top
- Sacrificial anode installed on 316 stainless shaft

CONTROL PANEL

- UL 508 Listed
- NEMA type 3R/4X thermoplastic enclosure
- Equipment-rated GFCI protection
- Surge protector
- Motor starter with adjustable overload
- Hand-Off-Auto switch
- 24-hour mechanical timers (fountains & lights)
- Terminal block wiring
- 5-wire power required (L1, L2, L3, N, G)

3.3HJF FOUNTAIN

OVERVIEW

HP	Voltage / Phase / Hz	Running Amps	Lock Rotor Amps	Suggested Pond Size (SA)	Min. Depth of Operation (in.)
3	460V / 3 / 60	5	31	Up to 1.5*	24"

*Surface Acreage; also consider pond shape, depth, and oxygen demand.

MODEL SPECIFICATIONS


Model	Cord Length (ft.)	Cord Gauge
3.3HJF050	50	14/4
3.3HJF100	100	14/4
3.3HJF150	150	14/4
3.3HJF200	200	14/4
3.3HJF250	250	14/4
3.3HJF300	300	14/4
3.3HJF400**	400	14/4
3.3HJF500**	500*	14/4

*500' and longer cords available by custom order only.


**Ships motor freight only.




INCLUDED PATTERNS




Birch
16' H x 12' W




Spruce
26' H x 12' W




Redwood
22' H x 6' W



Linden
(Blue Nozzle)
20.5' H x 38' W



Balsam
(Blue Nozzle)
19' H x 34' W

NOTE  For additional patterns, ask about Premium Nozzles.

