



4400HJF FOUNTAIN

OVERVIEW

- Complete package includes motor unit, control panel, float with screens, mooring lines, cable, four interchangeable nozzles.
- Cable is UL, CSA & NEC rated for underwater use.
- Total package Listed by ETL to UL/CSA standards.
- Intake near surface allows for shallow operation
- Saltwater compatible
- Packaged for convenient shipping
- Optional lighting available

FLOAT


- UV-resistant polyethylene
- Single-piece float
- Series 300 stainless steel hardware
- Thermoplastic protective bottom screen
- Two 50' braided nylon mooring ropes

FOUNTAIN COMPONENTS

- Custom thermoplastic impeller
- UV-resistant thermoplastic cone and fountain housing
- Series 300 stainless steel hardware
- Four thermoplastic nozzles (five patterns)
- Thermoplastic baseplate and housing
- Twist on/off nozzles for easy pattern changes

POWER CABLE

- 3 wire (L1, L2, G)
- Quick Disconnect standard on 12+ AWG cords (otherwise optional)
- Stainless steel strain relief on 12+ AWG cords
- 6' flex sleeving protection standard (optional for entire cord length)



Dimensions

Float width w/ brackets: 28"

Unit height with float: 18"

MOTOR UNIT

- 1HP, 208-240Vac operating voltage range, single phase
- 1750 RPM
- Oil cooled
- Continuous duty rated
- 17mm top and bottom bearings
- Thermal overload protection
- Fully unitized heavy-duty carbon-ceramic mechanical seal
- Series 300 stainless steel can
- Engineering grade thermoplastic top
- Sacrificial anode installed on 316 stainless shaft

CONTROL PANEL

- UL 508 Listed
- NEMA type 3R/4X thermoplastic enclosure
- 20 amp breaker
- Human-rated GFCI protection
- Surge protector
- 24-hour mechanical fountain timer
- Terminal block wiring
- 24-hour mechanical timer for optional lighting
- 4-wire power required (L1, L2, N, G)

4400HJF FOUNTAIN

OVERVIEW


HP	Voltage / Phase / Hz	Running Amps	Lock Rotor Amps	Suggested Pond Size (SA)	Min. Depth of Operation (in.)
1	208-240V / 1 / 60	5.3	20	Up to 1/2*	19"

*Surface Acreage; also consider pond shape, depth, and oxygen demand.

MODEL SPECIFICATIONS

Model	Cord Length (ft.)	Cord Gauge	Number of Boxes
4400HJF050	50	14/3	3
4400HJF100	100	14/3	3
4400HJF150	150	12/3	4
4400HJF200	200	12/3	4
4400HJF250	250	12/3	4
4400HJF300	300	12/3	4
4400HJF400	400	12/3	4
4400HJF500	500	12/3	4


*500' and longer cords available by custom order only.




Birch
11' H x 8' W




INCLUDED PATTERNS




Willow
9' H x 31' W



Sequoia
18' H x 11' W



Cypress
9' H x 28' W



Linden
12' H x 7' W (inner)
6' H x 31' W (outer)



NOTE For additional patterns, ask about Premium nozzles.

Kasco[®]

800 Deere Rd. Prescott, WI 54021

| 715.262.4488

| sales@kascomarine.com

| kascomarine.com

4400HJF FOUNTAIN CUT SHEET