



7.3HJF FOUNTAIN

OVERVIEW

- Complete package includes motor unit, control panel, float with screens, mooring lines, cable, five interchangeable nozzles
- Total package Listed by ETL to UL/CSA standards
- Intake near surface allows for shallow operation
- Saltwater compatible
- Packaged for convenient shipping
- Optional lighting available

FLOAT


- UV-resistant polyethylene
- Single-piece float
- Series 300 stainless steel hardware
- Series 300 stainless steel bottom screen
- Three 50' braided nylon mooring ropes

FOUNTAIN COMPONENTS

- Custom thermoplastic impeller
- UV-resistant thermoplastic cone and fountain housing
- Stainless steel base plate
- Series 300 stainless steel hardware
- Five thermoplastic nozzles
- Twist on/off nozzles for easy pattern changes

POWER CABLE

- 4 wire (L1, L2, L3, G)
- Quick Disconnect standard
- Stainless steel strain relief standard
- 6' protective stainless steel flex sleeving standard (optional for entire cord length)
- Cable is UL, CSA & NEC rated for underwater use



Dimensions

Float diameter: 47.5"

Unit height with float: 24"

MOTOR UNIT

- 7.5HP, 460Vac operating voltage range, three phase
- Class B insulation
- 1750 RPM
- Oil cooled
- Continuous duty rated
- 17mm top and 20mm bottom bearings
- Fully unitized heavy-duty carbon-ceramic mechanical seal
- Series 300 stainless steel can
- Cast stainless steel motor top
- Sacrificial anode installed on 316 stainless shaft

CONTROL PANEL

- UL 508 Listed
- NEMA type 3R/4X thermoplastic enclosure
- Equipment-rated GFCI protection
- Surge protector
- Motor starter with adjustable overload
- Hand-Off-Auto switch
- 24-hour mechanical timers (fountains & lights)
- Terminal block wiring
- 5-wire power required (L1, L2, L3, N, G)

7.3HJF FOUNTAIN

OVERVIEW

HP	Voltage / Phase / Hz	Running Amps	Lock Rotor Amps	Suggested Pond Size (SA)	Min. Depth of Operation (in.)
7.5	460V / 3 / 60	10	49	3.5*	28"

*Surface Acreage; also consider pond shape, depth, and oxygen demand.

MODEL SPECIFICATIONS


Model	Cord Length (ft.)	Cord Gauge
7.3HJF100**	100	14/4
7.3HJF150**	150	14/4
7.3HJF200**	200	14/4
7.3HJF250**	250	12/4
7.3HJF300**	300	12/4
7.3HJF400**	400	12/4
7.3HJF500**	500*	10/4

*500' and longer cords available by custom order only.


**Ships motor freight only.



INCLUDED PATTERNS




Birch
26' H x 16' W




Spruce
34' H x 12' W




Redwood
36' H x 8' W



Linden
(Blue Nozzle)
26' H x 46' W



Balsam
(Blue Nozzle)
21' H x 36' W

NOTE  For additional patterns, ask about Premium Nozzles.

