

LARGE 50 HZ EJ SERIES FOUNTAIN

OVERVIEW

- · Complete package includes motor unit, float with screens, mooring lines, cable, four interchangeable nozzles.
- Rubber 10m power cord or 1m stub cord
- CE Marked
- Intake near surface allows for shallow operation
- Saltwater compatible
- · Packaged for convenient shipping
- Optional lighting available

FLOAT

- UV-resistant polyethylene
- Single-piece float
- Series 300 stainless steel hardware
- Series 300 stainless steel bottom screen
- Three 15m braided mooring ropes

FOUNTAIN COMPONENTS

- Custom thermoplastic impeller
- UV-resistant thermoplastic cone and fountain housing
- Series 300 stainless steel hardware
- Four thermoplastic nozzles (fiver patterns)
- Twist on/off nozzles for easy pattern changes

POWER CABLE

- 1m stub cord
- Rubber jacket, 3-conductor power cord with earth conductor
- Potted guick disconnect and stainless steel strain relief standard on all stub cords
- Flex sleeve cord protection
- Wire size: 2.5mm² for all cord lengths



MOTOR UNIT

- 5HP, 380V 3-phase
- Class B insulation
- 1450 RPM
- Oil cooled
- Continuous duty rated
- Long-life bearings
- Thermal overload protection
- Fully unitized heavy-duty carbon-ceramic mechanical seal
- Series 300 stainless steel can
- Cast stainless steel motor top
- Sacrificial anode installed on 316 stainless shaft

OPTIONAL LIGHTS


- 230V, 50Hz compatible
- Ultrasonic welded watertight composite housing with 5 colored lenses
- Includes light fixtures and stub cord

LARGE 50 HZ EJ SERIES FOUNTAIN

OVERVIEW

Model	НР	Voltage / Phase / Hz	Amperage	Locked Rotor Amps	Suggested Pond Size (m²)	Min. Depth of Operation
5.3EHJF	5	380 / 3 / 50	7.7	27	10,000	71cm





Linacii			
HP	Height	Width	
5	6.2m	12.2m	



Baisam			
HP	Height	Width	
5	4.7m	9.4m	



	_	
HP	Height	Width
5	5.8m	3m



Sprace			
HP	Height	Width	
5	7.9m	2.7m	



Redwood			
HP	Height	Width	
5	8.1m	1.8m	

NOTE For additional patterns, ask about Premium nozzles.