

UNIT MOUNTING OPTIONS

MOUNT KITS

Secure your Kasco unit to a dock, pier, walkway, or other in-water structure. Choose your desired depth, angle, and flow of water to achieve desired results.

Universal Kits

- For 1/2, 3/4, and 1HP units
- Requires 1 in. / 25 DN nominal threaded / unthreaded pipe

Industrial Kits

- For 1/2, 3/4, 1, and 2HP units
- Requires 1.5 in. / 40 DN nominal threaded / unthreaded pipe



Universal Kit

Industrial Kit



U-bolt Kit Prevents Drilling into Structure (Purchased separately)



Simple Swivel Directs Water to Desired Area (Included with kit)



Multiple Angles of Unit Orientation



Lifetime Warranty

HORIZONTAL FLOAT

Suspend your AquatiClear Circulator below the water's surface and safely anchor it to shore. Using stainless steel hardware and components, the float accommodates 1/2, 3/4, and 1HP units.



3 Tie-Down Loops for Secure Installation



Power Cord Strain Relief Clip Included



3 Angles of Unit Orientation



3-Year Warranty



| PART # | DESCRIPTION | UNITS COMPATIBLE | MSRP |
|---------|---|--|-------|
| 243478 | Universal Mount with Simple Swivel bracket (patent pending) | 1/2, 3/4, and 1HP units | \$372 |
| 243479 | Industrial Mount with Simple Swivel bracket (patent pending) | 1/2, 3/4, 1, and 2HP units in harsh conditions | \$616 |
| 997108K | U-Bolt Kit for Universal and Industrial Kits (allows installation without drilling) | 1/2, 3/4, and 1HP units | \$18 |
| 213001 | Horizontal Float with tie-down loops | 1/2, 3/4, and 1HP units | \$500 |

^{*} Simple Swivel bracket is patent pending.

Product Notes:

^{1.} For Universal and Industrial Kits, customer supplies hardware to secure mount. Customer also supplies pipe that does not exceed 10 ft.