

1/2HP, 3/4HP, & 1HP

SURFACE AERATOR

- 120V and 208 240V, single phase options1-piece float blends with the water's surface and is easy to install
- Manage from shore with optional human-rated, GFCI-protected control panel. See page 54.





Lighting Packages Available



Shallow Operating Depths*



2-Year Warranty



ETL Listed to UL & CSA Standards

| шъ | MODEL | CORD LENGTH | | | | | | | | | |
|-----------------------------|-------------------|-------------|---------|----------|-------------|-----------|---------|---------|---------|---------|---------|
| HP | | 25 FT | 50 FT | 75 FT | 100 FT | 150 FT | 200 FT | 250 FT | 300 FT | 400 FT | 500 FT |
| 120V, SINGLE PHASE PACKAGES | | | | | | | | | | | |
| | 2400A | \$946 | \$988 | - | \$1,161 | \$1,725 | \$1,977 | - | - | - | - |
| 1/2 | 2400AF | - | \$1,239 | - | \$1,414 | \$1,971 | \$2,221 | - | - | - | - |
| | 2400AF (BTM SCR) | - | \$1,481 | - | \$1,656 | \$2,213 | \$2,463 | - | - | - | - |
| | 3400A | \$1,008 | \$1,051 | - | \$1,209 | \$1,811 | \$2,036 | - | - | - | - |
| 3/4 | 3400AF | - | \$1,325 | - | \$1,492 | \$2,076 | \$2,333 | - | - | - | - |
| | 3400AF (BTM SCR) | - | \$1,567 | - | \$1,734 | \$2,318 | \$2,575 | | - | - | - |
| | 4400A | \$1,118 | \$1,206 | \$1,314 | \$1,726 | \$2,366 | \$2,744 | - | - | - | - |
| 1 | 4400AF | - | \$1,620 | \$1,730 | \$2,178 | \$2,790 | \$3,218 | - | - | - | - |
| | 4400AF (BTM SCR) | - | \$1,862 | \$1,972 | \$2,420 | \$3,032 | \$3,460 | - | - | - | - |
| | | | | 208-240V | , SINGLE PH | ASE PACKA | GES | | | | |
| | 3400HA | - | \$1,124 | - | \$1,262 | \$1,896 | \$2,097 | \$2,251 | \$2,352 | \$2,847 | Inquire |
| 3/4 | 3400HAF | - | \$1,385 | - | \$1,522 | \$2,145 | \$2,346 | \$2,491 | \$2,590 | \$3,074 | Inquire |
| | 3400HAF (BTM SCR) | - | \$1,627 | - | \$1,764 | \$2,387 | \$2,588 | \$2,733 | \$2,832 | \$3,316 | Inquire |
| | 4400HA | - | \$1,302 | - | \$1,435 | \$2,123 | \$2,337 | \$2,647 | \$2,760 | \$3,057 | Inquire |
| 1 | 4400HAF | - | \$1,625 | - | \$1,770 | \$2,407 | \$2,648 | \$2,869 | \$2,980 | \$3,075 | Inquire |
| | 4400HAF (BTM SCR) | - | \$1,867 | - | \$2,012 | \$2,649 | \$2,890 | \$3,111 | \$3,222 | \$3,317 | Inquire |

^{*1/2}HP can operate in 17.5 in. of water. 3/4HP can operate in 17.5 in. of water. 1HP can operate in 19 in. of water. Product Notes:

- 1. Prices in bold have quick disconnect installed on power cords.
- 2. Part # is the model combined with cord length (ex. 2400AF050).
- 3. "A" models only include motor unit; "AF" models include unit and float; "BTM SCR" models include unit, float, and bottom screen.
- 4. Solar-powered option available. Contact Kasco for details.





2HP, 3HP, & 5HP

SURFACE AERATOR

- 208 240V, single and three phase options
- Control panels are optional for single phase units and included for three phase units except "U" models.
- Control panels feature human-rated GFCI protection. See page 54.







Shallow Operating Depths*



3-Year Warranty**



ETL Listed to UL & CSA Standards

| НР | MODEL | CORD LENGTH | | | | | | | | | |
|---------------------------------|--------------------------------|-------------|---------|---------|---------|---------|----------|----------|---------|--|--|
| | | 50 FT | 100 FT | 150 FT | 200 FT | 250 FT | 300 FT | 400 FT | 500 FT | | |
| 208-240V, SINGLE PHASE PACKAGES | | | | | | | | | | | |
| 2 | 8400A | \$2,204 | \$2,760 | \$2,970 | \$3,171 | \$3,405 | \$4,513 | \$8,545 | Inquire | | |
| | 8400AF | \$3,429 | \$3,996 | \$4,200 | \$4,404 | \$4,609 | \$5,640 | \$9,008 | Inquire | | |
| | 8400AF (BTM SCR) | \$3,671 | \$4,238 | \$4,442 | \$4,646 | \$4,851 | \$5,882 | \$9,250 | Inquire | | |
| | 3.1A | \$2,980 | \$3,275 | \$3,688 | \$4,542 | \$4,875 | \$5,196 | \$8,938 | Inquire | | |
| 3 | 3.1AF | \$4,317 | \$4,795 | \$4,963 | \$5,597 | \$5,842 | \$6,240 | \$9,903 | Inquire | | |
| | 3.1AF (BTM SCR) | \$4,559 | \$5,037 | \$5,205 | \$5,839 | \$6,084 | \$6,482 | \$10,145 | Inquire | | |
| | 5.1A | - | \$4,468 | \$5,254 | \$5,888 | \$7,223 | \$9,741 | \$12,613 | Inquire | | |
| 5 | 5.1AF | - | \$5,688 | \$6,524 | \$7,161 | \$8,447 | \$10,702 | \$12,969 | Inquire | | |
| | 5.1AF (BTM SCR) | - | \$5,930 | \$6,766 | \$7,403 | \$8,689 | \$10,944 | \$13,211 | Inquire | | |
| | 208-240V, THREE PHASE PACKAGES | | | | | | | | | | |
| | U2.3A | \$2,916 | \$3,120 | \$3,520 | \$3,751 | \$4,337 | \$4,758 | \$6,852 | Inquire | | |
| 2 | U2.3AF | \$4,225 | \$4,419 | \$4,808 | \$5,033 | \$5,618 | \$6,012 | \$8,003 | Inquire | | |
| | U2.3AF (BTM SCR) | \$4,467 | \$4,661 | \$5,050 | \$5,275 | \$5,860 | \$6,254 | \$8,245 | Inquire | | |
| | U3.3A | \$3,556 | \$3,778 | \$4,185 | \$4,660 | \$4,853 | \$6,312 | \$7,663 | Inquire | | |
| 3 | U3.3AF | \$4,895 | \$5,103 | \$5,504 | \$5,952 | \$6,127 | \$7,548 | \$8,960 | Inquire | | |
| | U3.3AF (BTM SCR) | \$5,137 | \$5,345 | \$5,746 | \$6,194 | \$6,369 | \$7,790 | \$9,202 | Inquire | | |
| | U5.3A | - | \$4,426 | \$5,089 | \$5,798 | \$6,604 | \$9,610 | \$11,028 | Inquire | | |
| 5 | U5.3AF | - | \$5,823 | \$6,476 | \$7,235 | \$7,971 | \$10,834 | \$11,965 | Inquire | | |
| | U5.3AF (BTM SCR) | - | \$6,065 | \$6,718 | \$7,477 | \$8,213 | \$11,076 | \$12,207 | Inquire | | |

^{*2}HP can operate in 20 in. of water. 3HP can operate in 24 in. of water. 5HP can operate in 26 in. of water.

Product Notes:

1. See notes on next page.



^{**} Extended warranty available on 2HP and 5HP units.

| НР | MODEL | CORD LENGTH | | | | | | | | | |
|--|-----------------|-------------|---------|---------|----------|----------|----------|----------|---------|--|--|
| | | 50 FT | 100 FT | 150 FT | 200 FT | 250 FT | 300 FT | 400 FT | 500 FT | | |
| 208-240V, THREE PHASE PACKAGES (INCLUDES CA-3235 CONTROL PANELS) | | | | | | | | | | | |
| | 2.3AF | \$7,288 | \$7,482 | \$7,871 | \$8,094 | \$8,680 | \$9,075 | \$11,065 | Inquire | | |
| 2 | 2.3AF (BTM SCR) | \$7,530 | \$7,724 | \$8,113 | \$8,336 | \$8,922 | \$9,317 | \$11,307 | Inquire | | |
| | 3.3AF | \$7,962 | \$8,170 | \$8,571 | \$9,020 | \$9,194 | \$10,614 | \$12,027 | Inquire | | |
| 3 | 3.3AF (BTM SCR) | \$8,204 | \$8,412 | \$8,813 | \$9,262 | \$9,436 | \$10,856 | \$12,269 | Inquire | | |
| _ | 5.3AF | - | \$8,972 | \$9,624 | \$10,384 | \$11,121 | \$13,882 | \$15,115 | Inquire | | |
| 5 | 5.3AF (BTM SCR) | - | \$9,214 | \$9,866 | \$10,626 | \$11,363 | \$14,124 | \$15,357 | Inquire | | |

Product Notes:

- 1. Prices in bold have quick disconnect installed on power cords.
- 2. Part # is the model combined with cord length (ex. U2.3AF050).
- 3. "A" models only include motor unit; "AF" models include unit and float; "BTM SCR" models include unit, float, and bottom screen.
- 4. If adding a light kit to a three phase unit, an additional control panel is needed. Contact Kasco for details.
- 5. 2, 3, and 5HP, three phase units are constructed with a durable stainless steel motor top for reliable performance in all environments.
- 6. 460 480V, three phase option available for special order in approved locations only. Contact Kasco for details.

